

# SANDBLASTER®



## SELF-CLEANING WITH FACTORY FUSING NSF CONSTRUCTION WITH SURFACE-MOUNTED THERMOSTATS

### 3-Year Limited Warranty

All models meet or exceed the Thermal Efficiency and/or standby loss requirements of the U.S. Department of Energy and Current Edition of ASHRAE/IESNA 90.1.

Model Number	Gallon Capacity	Kilowatt Input	No. of Elements	Standard Voltage	Diameter (Inches)	Height (Inches)	Hi Cube Trailer Load Factor	Approximate Shipping Weight	Net Distributor Price
CSB 52 6 SFE	50	6	3	208	21¾	55¼	1.19	260	\$ 2,091
CSB 52 9 SFE	50	9	3	208	21¾	55¼	1.19	260	2,228
CSB 52 12 SFE	50	12	3	208	21¾	55¼	1.19	260	2,236
CSB 52 135 SFE	50	13.5	3	208	21¾	55¼	1.19	260	2,277
CSB 52 15 SFE	50	15	3	208	21¾	55¼	1.19	260	2,277
CSB 52 18 SFE	50	18	3*	208	21¾	55¼	1.19	260	2,309
CSB 52 24 SFE	50	24	6	208	21¾	55¼	1.19	265	3,357
CSB 52 27 SFE	50	27	6	208	21¾	55¼	1.19	265	3,405
CSB 52 30 SFE	50	30	6	208	21¾	55¼	1.19	265	3,454
CSB 52 36 SFE	50	36	6*	208	21¾	55¼	1.19	265	3,502
CSB 82 6 SFE	80	6	9	208	25¼	59½	1.85	280	2,734
CSB 82 9 SFE	80	9	3	208	25¼	59½	1.85	280	2,792
CSB 82 12 SFE	80	12	3	208	25¼	59½	1.85	280	2,801
CSB 82 135 SFE	80	13.5	3	208	25¼	59½	1.85	280	2,875
CSB 82 15 SFE	80	15	3	208	25¼	59½	1.85	280	2,875
CSB 82 18 SFE	80	18	3*	208	25¼	59½	1.85	280	2,895
CSB 82 24 SFE	80	24	6	208	25¼	59½	1.85	280	3,725
CSB 82 27 SFE	80	27	6	208	25¼	59½	1.85	280	3,986
CSB 82 30 SFE	80	30	6	208	25¼	59½	1.85	280	4,024
CSB 82 36 SFE	80	36	6*	208	25¼	59½	1.85	280	4,046
CSB 82 405 SFE	80	40.5	9	208	25¼	59½	1.85	280	5,053
CSB 82 45 SFE	80	45	9	208	25¼	59½	1.85	280	5,053
CSB 82 54 SFE	80	54	9	208	25¼	59½	1.85	280	5,085
CSB 120 6 SFE	119	6	3	208	35¾	59½	2.08	390	3,172
CSB 120 9 SFE	119	9	3	208	35¾	62¼	2.08	390	3,259
CSB 120 12 SFE	119	12	3	208	35¾	62¼	2.08	390	3,279
CSB 120 135 SFE	119	13.5	3	208	35¾	62¼	2.08	390	3,320
CSB 120 15 SFE	119	15	3	208	35¾	62¼	2.08	390	3,320
CSB 120 18 SFE	119	18	3*	208	35¾	62¼	2.08	390	3,359
CSB 120 24 SFE	119	24	6	208	35¾	62¼	2.08	390	4,335
CSB 120 27 SFE	119	27	6	208	35¾	62¼	2.08	390	4,353
CSB 120 30 SFE	119	30	6	208	35¾	62¼	2.08	390	4,389
CSB 120 36 SFE	119	36	6*	208	35¾	62¼	2.08	390	4,408
CSB 120 405 SFE	119	40.5	9	208	35¾	62¼	2.08	390	5,612
CSB 120 45 SFE	119	45	9	208	35¾	62¼	2.08	390	5,612
CSB 120 54 SFE	119	54	9	208	35¾	62¼	2.08	390	5,657

\*Models will be shipped with three less elements on voltages other than 208 voltage.

For 277 and 480 volt, add \$51.00 to the Distributor Price. For ASME Tank Construction, add \$393.00 to the above prices and "A" to the model number. Shipping weight will increase 50 pounds with ASME construction. ASME Models are design certified for a maximum allowable working pressure of 160 psi. All above prices include a shipped with ASME rated Temperature and Pressure Relief Valve. Field conversion kits allow easy change of voltage and kw inputs.

Model Number	Loading Percentage 53'	Full Truck Load 53'	Voltage	Model Number Suffix	Price Each
CSB 52	1.00	100	208	X	—
CSB 82	2.08	48	277	Y	\$ 51
CSB 120	2.22	45	480	B	51

Sandblaster Electric models are available in standard and ASME tank construction as well as 240, 208, 277 and 480 volt. 208V, 240V and 480V available three-phase only. Field convert to single-phase. 277 volt models are shipped single phase only. When ordering please specify total kw and number of elements.

### Electric Manifold Kits

Manifold Kit Description	Part Number	Net Distributor Price
Dual Manifold Kit	9003429205	\$ 845
Triple Manifold Kit	9003430205	1,605
Quad Manifold Kit	9003431205	2,049

Note: These kits are for use with CSB 52, 82 and 120 models only.



