

INDUSTRIAL STEATITE

500 to 1500 L



Electric water heater



INSPECTION FLANGE



ENAMELLED STEEL TANK

- EACH HEATING ELEMENT IS 230 V/400 V TRIPHASE. THEY HAVE A STEATITE DRY HEATING ELEMENT WITH A LOW WATT DENSITY, WHICH ENTAILS A LOWER SURFACE TEMPERATURE TO KEEP MAINTENANCE DOWN TO A MINIMUM. IN FACT, THEY ARE "LIMESCALE-PROOF".
- HEATING ELEMENTS FACING DOWN TO PROVIDE THE USER WITH A GREATER VOLUME OF HOT WATER.
- FLEXIBILITY: MODULAR SYSTEM WHICH ALLOWS FOR AN EASY INCREASE IN THE POWER OF THE PRODUCT BY MERELY ADDING MORE HEATING ELEMENTS.
- EASY MAINTENANCE: INSPECTION FLANGE FOR EASY MAINTENANCE OF THE WATER HEATERS.
- DOUBLE THERMOSTAT INCLUDED (RELAY IS NOT SUPPLIED).

**steatite
resistance**

Technical data - Overall dimensions

		PERFO PLUS 500	PERFO PLUS 750	PERFO PLUS 1000	PERFO PLUS 1500					
Capacity	l	500	750	1000	1500	a mm	630	790	790	1100
Power	kW	9	15	15	30	b mm	730	890	890	1200
Heating Time	h,min	4,00	3,30	4,40	3,30	c mm	1846	1751	2104	1880
Dispersions	kWh/24h	7	6	6,9	9,2	d mm	719	661	661	710
Net weight	kg	135	205	235	345	e mm	70	105	105	135
						f mm	390	470	470	625
						g mm	860	1020	1020	1330
						ef mm	M1' 1/2	M1' 1/2	M1' 1/2	M2'
						ec mm	M2'	M2'	M2'	M2'
						r mm	M1' 1/4	M1' 1/4	M1' 1/4	M1' 1/4

PERFO PLUS 500
398210

PERFO PLUS 750
398211

PERFO PLUS 1000
398212

PERFO PLUS 1500
398213

